

Original post set 1820 by John Hendricks with witness: 6" beech S 26 E 11 links; 18" ash N 88 W 23 links per Marion County Atlas pg. 13. Survey by Wm. P. Smith 1-3-1867 indicates no stone nor witness per Franklin Township Legal Survey Book pg. 12. MC SO 1948 called boat spike. MC SO 1952 called a cut cross. Monroe 11-30-54 called an iron pin. Monroe 4-7-59 called the same. McLand 5-11-72 called boat spike. Jacobs 8-1-87 called a road nail. Wilcoxen 12-28-87 called a PK nail. Wilcoxen 1-6-94 called a PK nail w/washer. Wilcoxen 7-22-98 called a PK nail w/washer. Excavated by Wilcoxen 6-28-01 and PK nail was found 3" down. A boat spike fd 6" dn. No other references were fd. Harrison set. Re-tied 4-30-08 by Wilcoxen. 14050401

REF.	DISTANCE	DESCRIPTION
1.	27.62'	Mag nail w/shiner top wooden guard rail post
2.	18.63'	Mag nail w/shiner top wooden guard rail post
3.	22.70'	Mag nail w/shiner top wooden guard rail post
4.	150'+/-	Due W to F-end of bridge over 1-74
5.	24.57'	Mag nail w/shiner top wooden guard rail post